

# 台北信義機房 Taipei Xinyi IDC

## Tier III Design

信義IDC位於台灣行政中樞，週邊除了政府機關林立，也聚集許多商業及金融產業；信義IDC不僅擁有數個高規格機房，更是中華電信網路、IDC、雲端、SOC等服務團隊總部，能第一時間提供您最完善的專業服務。

Surrounded by government agencies and many commercial related industries, Xinyi IDC is located in the administrative center of Taiwan. It not only consists of several high standard data centers, but also has the core teams of CHT HiNet, IDC, Cloud, and SOC services. With these advantages, Xinyi IDC is able to provide the most complete professional services for enterprise customers.

### HiNet/HiLink總部及骨幹節點，提供最順暢、寬廣的頻寬資源

The headquarters and backbone nodes of HiNet and HiLink. Provide the smoothest and most comprehensive bandwidth resources.

### 機房電力及空調以認證機房規格打造，並提供7x24全天候維運服務

The electricity and air conditioning are built with certified specifications. Provide 7x24 operation and maintenance services.

### 20年以上IDC專業服務經驗，客群涵蓋政府、金融及各式內容業者，可依客戶需求彈性客製化機房

CHT has 20+ years of IDC professional service experience. The customer base covers government, financial, and various CDN industries. Provide customized services based on customer demand.



## 台北市中正區

### Zhongzheng District, Taipei City

- 3分鐘可達捷運中正紀念堂站/東門站  
3 minutes from MRT Chiang Kai-shek Memorial Hall Station / Dongmen Station
- 6分鐘可達高鐵台北站/台北車站  
6 minutes from HRS/ TRA Taipei Station
- 18分鐘可達松山機場  
18 minutes from Taipei Songshan Airport

設施 Facility	
建物 Building	3棟11層以上建物 3 buildings with 11+ floors each
容量 Capacity	3,000櫃以上/3,000 racks
地板載重 Floor Loading	400~700 kg/m <sup>2</sup>
耐震 Seismic Rating	225~338gal
高架地板高度 Raised Floor Height	25-55cm
機櫃規格 Rack Size	45U (120cm x 60cm) / 42U (90-120cm x 60cm)

網路及服務 Connectivity & Service	
網路 Networks	HiNet骨幹節點、資料中心互連服務(DCI) HiNet backbone nodes, DCI (Data center Interconnect)
進線孔及樓內路徑 Diversity	單進線孔、樓內單路由 1 entry point with single in-building path
其他固網進線 Carrier Availability	專案申請/Project application
雲端服務接取 Cloud Access	N/A
智慧幫手 Smart Hands	7x24

安全 Security	
保全人員 Security Officers	7x24
監視錄影 Cameras	24小時監視錄影，出入口影像保存6個月 其他影像保存3個月 24-hour surveillance video, 6 months for entrance and exit images, 3 months for other images
門禁管控 Access Control	門禁卡與生物特徵辨識管制 Key cards and biometric scanners
火警偵測 Fire Detection	VESDA極早期預警智能探測器
滅火類型 Fire Suppression	HFC-227ea、FM200、NAFS-125 氣體式自動滅火系統

電力 Power	
發電機 Generator	N+1
不斷電系統 UPS	2N
電力供應 Power Provision	標準機櫃雙迴路供電共3~4KW / 單迴路供電2KW Support 3-4KW primary and redundant or 2KW primary configurations for standard racks.
儲油運轉時間 Fuel Storage	18-36小時 (依機房負載情況而定) 18-36 hours (depends on the loading)
機櫃電源排插規格 Rack PDU Spec	NEMA 5-15R / L5-30R / L6-30R

#### 認證標章



IDC官網

\* 機房規格及認證以各機房現場實際提供資料為準 All specs and certificates are subject to the actual info provided by each data center.